

PMD-326C

Box Contents

Contenido de la caja



Contenu de la boîte

Contenuti della confezione



Lieferumfang



Important: Visit marantzpro.com and find the webpage for **PMD-326C** to download the complete *User Guide*.

Importante: Visite en marantzpro.com la página correspondiente al **PMD-326C** para descargar la *Guía de usuario* completa.

Important : Visitez marantzpro.com pour trouver la page Web du **PMD-326C** afin de télécharger son *Guide d'utilisation* complet.

Importante: recarsi su marantzpro.com e trovare la pagina di **PMD-326C** per scaricare la *Guida per l'uso* completa.

Wichtig: Besuchen Sie marantzpro.com und suchen Sie die Webseite für **PMD-326C**, um das komplette *Benutzerhandbuch* herunter zu laden.

Technical Specifications

Especificaciones técnicas

Spécifications techniques

Specifiche tecniche

Technische Daten

System	CD player		
Compatible Media	CD, USB device (mass storage class)		
Supported Device/File Formats & Systems	CD	CD-DA (CD text), CD-ROM (ISO 9660), MP3 CD	
	USB	FAT16, FAT32	
	MP3	Format: MPEG1 Audio Layer 3 File extension: .mp3	Sample rate: 44.1 kHz Bit rate: 32–320 kbps & VBR
Number of Channels	1 (stereo), 2 (mono)		
Audio Frequency Range	20 Hz – 20 kHz (± 1.0 dB)		
Signal-to-Noise Ratio	>95 dB (A-weighted)		
Total Harmonic Distortion	<0.01%		
Dynamic Range	>85 dB		
Channel Separation	>80 dB		
Analog Outputs L/R (unbalanced)	Type: RCA terminal	Load Impedance: >10 k Ω	Output Level: 2 Vrms @ 10 k Ω load
Analog Outputs L/R (balanced)	Type: XLR	Load Impedance: >10 k Ω	Output Level: +4 dBu
Aux Input	Type: 1/8" (3.5mm) TRS terminal Input Impedance: > 10 k Ω		Maximum Input Level: 1 Vrms Maximum Output Level: 3 Vrms
File/Folder Limits	Storage Capacity: up to 2 TB File Size: up to 2 GB File Name Length: up to 255 characters		Number of Files: up to 999 (for 1 folder) Folder Name Length: up to 255 characters
Power	USA & Canada: 120 V AC, 60 Hz Europe & Asia Pacific Region: 240 V AC, 50/60 Hz Japan: 100 V AC, 50/60 Hz		Power Consumption: 30 W
Environmental Conditions	Operating Temperature: 41 – 95 °F (5 – 35 °C)		Operating Humidity: 25–85% (no condensation)
Dimensions (width x depth x height)	19.00" x 13.66" x 1.73" (with rack ears)		17.09" x 13.66" x 1.73" (without rack ears)
	483 x 347 x 44 mm (with rack ears)		434 x 347 x 44 mm (without rack ears)
Weight	7.94 lbs.		3.6 kg